

PLEASE READ THIS LABEL CAREFULLY BEFORE STARTING YOUR PROJECT



WARNING!! COMBUSTIBLE VAPOR AND LIQUID. CONTAINS PETROLEUM NAPHTHA. KEEP AWAY FROM HEAT AND FLAME AND ALWAYS PREVENT A BUILD-UP OF VAPORS. DO NOT BREATHE VAPORS. VAPOR HARMFUL AND MAY AFFECT BRAIN OR CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES IRRITATION OF EYE, NOSE, THROAT AND SKIN. USE ONLY WITH ADEQUATE VENTILATION. Ensure adequate fresh air while using product. If eye watering, headache, or dizziness is experienced, or concentration of vapors is above applicable limits, use a NIOSH approved; properly fitted respirator, following manufacturer's recommendations. Avoid contact with skin, eyes or clothing and wash thoroughly after use. Close container after each use.

FIRST AID: In case of eye contact flush immediately with plenty of fresh water for at least 15 minutes, seek immediate medical attention. In case of skin contact, wash thoroughly with soap and water. **If swallowed DO NOT INDUCE VOMITING*** - seek immediate medical attention. If difficulty in breathing is experienced, move to fresh air. If continued difficulty is experienced, seek immediate medical assistance.

***NOTE TO PHYSICIAN:** Ingestion of this product or subsequent vomiting can result in aspiration of light hydrocarbon liquids, which can cause pneumonitis.

SPONTANEOUS COMBUSTION HAZARD

THIS PRODUCT CAN CATCH FIRE SPONTANEOUSLY! To avoid spontaneous combustion of rags, pads, rollers, brushes or clothing that may have come into contact with this product, soak them in water after use and place them in a sealed metal container away from buildings. Dispose of rags; etc., and unused product in accordance with local regulations.


NOT FOR USE ON SLOPING ROOF SURFACES

Application of sealers to sloping roof surfaces is inherently dangerous as falling from roofs can result in serious, permanent injury or death. Sun Frog Exterior Sealer Finish & Stain will make wood roofs extremely slippery during application and is not advised for self-application on sloping roof surfaces.

WARNING!! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH- approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424- LEAD or log on to www.epa.gov/lead

THIS PRODUCT CONTAINS LESS THAN 250 GRAMS PER LITERS VOC AND COMPLIES WITH EXISTING POLLUTION CONTROL REGULATIONS. DO NOT THIN PRIOR TO USE.

Sun Frog Products, Inc. West Linn, OR 97068 503/699-1162
Information, SDS and Material Safety Data Sheets available at www.sunfrogwoodsealers.com



ADDITIONAL QUESTIONS?

Visit our website at www.sunfrogwoodsealers.com
We can help protect your pad!




COVERAGE GUIDELINES: New, smooth sawn woods- 225-275 sq.ft. per gal. Older, weathered and roughsawn woods- 150 sq. ft. per gal.

CLEAN UP DIRECTIONS
After application, clean up tools, brushes, rollers, etc., with Mineral Spirit (Paint Thinner) or warm water and soap.

SUN PROTECTED



WATER TIGHT



EXTERIOR WOOD SEALER, FINISH & STAIN

PENETRATING OIL FORMULA

FOR DECKS, SHINGLES, SIDING & LOGS

ALSO GREAT FOR FENCES, GAZEBOS, FURNITURE, PLANTERS, ETC.

PROTECTS AND BEAUTIFIES ALL NATURAL EXTERIOR WOODS



***Higher & better solids & less solvent = Better protection and less pollution!**

*** Moisturizing oils retard weather damage and enhance wood's natural beauty.**

***Superior water repellency to help prevent warping and splitting.**

ONE GALLON

DANGER!! COMBUSTIBLE AND HARMFUL OR FATAL IF SWALLOWED
See WARNING on side label. KEEP OUT OF REACH OF CHILDREN

3.78 LITERS

LIMITED WARRANTY
Performance satisfaction is warranted for one year on decks and horizontal surfaces (six months for Mahogany and other hard woods) and for two years on siding, shingles and vertical surfaces, but only when used strictly in accordance with label directions. Sun Frog Corporation's liability under this warranty is strictly limited to replacement of product used, when shown to be defective, and it does not include any liability for labor or consequential damages of any kind arising from its use. It is the user's responsibility to determine the safety and suitability of use for this product. Failure to apply this product as directed voids this warranty. Customer must also provide proof of purchase receipts and submit "before and after" pictures of their project and the use of this product on it as substantiation for any Warranty Claim to be considered by Sun Frog Products, Inc. Sun Frog Corporation shall not be held responsible in any manner for personal injury, property damage, or other type of loss resulting from proper or improper storage, handling or use of this product.

COVERAGE GUIDELINES: New, smooth sawn woods- 225-275 sq.ft. per gal. Older, weathered and roughsawn woods- 150 sq. ft. per gal.

CLEAN UP DIRECTIONS
After application, clean up tools, brushes, rollers, etc., with Mineral Spirit (Paint Thinner) or warm water and soap.

PLEASE READ THIS LABEL CAREFULLY BEFORE STARTING YOUR PROJECT

PRODUCT DESCRIPTION: Sun Frog Exterior Sealer Finish & Stain is a penetrating wood finish incorporating a strong blend of moisturizing, sun resistant oils and water repellent solids, transparent oxide UV absorbing pigmentation, and other special protective ingredients. It includes a Broad Spectrum Biocide to protect the sealer from unsightly mold growth. OUR SEALER seals in oils to seal out water and other wood degrading elements. When properly applied, OUR SEALER leaves your wood looking PROTECTED yet NATURAL.

OUR SEALER IS DESIGNED FOR: Natural wood decks, siding, shingles, log homes, fences, gazebos, furniture, planter boxes, spa jackets and other exterior, unpainted, unstained wood surfaces. It is not a below ground preservative.

WOOD PREPARATION: Wood must be clean, porous (penetrable) and DRY prior to applying our SEALER. New woods showing dirt should be first cleaned with a mild detergent, rinsed and allowed to re-dry. Use Sun Frog's DECK CLEANER where existing wood is weathered or prior penetrating sealers have been used. Use Sun Frog DECK STRIPPER where prior surface film finishes, sealer excesses, paints or solid stains exist. After cleaning or stripping we recommend using Sun Frog's BORN AGAIN to restore maximum original wood color prior to sealing. Allow existing woods to re-dry after preparation but prior to sealing. **New woods, unless kiln dried (or already physically light when laid down), should generally be allowed thirty days of dry conditions prior to sealing.**

APPLICATION: MIX WELL BEFORE AND DURING APPLICATION. APPLY TO DRY WOOD ONLY AND ONLY WHEN EXTERIOR TEMPERATURE IS ABOVE 50°F BUT BELOW 90°F. IN ORDER OF EFFECTIVENESS, APPLY WITH A BRUSH, STAIN PAD OR ROLLER. IF SPRAYED (LEAST EFFECTIVE), USE A NIOSH APPROVED RESPIRATOR (see VAPOR WARNING in CAUTIONS section) AND BACK-BRUSH, BACK-PAD OR BACK-ROLL. OUR SEALER MUST PENETRATE THE WOOD TO ACHIEVE MAXIMUM PERFORMANCE AND AESTHETIC ENHANCEMENT, SO APPLY AS MUCH SEALER AS THE WOOD WILL ABSORB VIA ONE APPLICATION ONLY. "WET ON WET" SECONDS CAN BE ADDED ONLY IF THE ADDITIONAL SEALER IS LIKELY TO SOAK IN. DO NOT APPLY A SECOND COAT OVER A DRY FIRST COAT (OR A FIRST COAT OVER A PRIOR FINISH NOT FULLY REMOVED), AS LACK OF PENETRATION, OILINESS, SLOW DRY TIME, POSSIBLE TRACKING ISSUES AND INFERIOR LONG TERM AESTHETICS ARE LIKELY TO OCCUR. IMPORTANT: ON DECKS AND OTHER SMOOTH SAWN OR HORIZONTAL SURFACES, LIGHTLY RAG OFF ANY WET EXCESS EXISTING AFTER 1 to 2 HOURS OF DRY TIME (GENERAL RULE: "WHAT DOESN'T GET IN, GET OFF"), DISPOSING OF OILY RAGS CAREFULLY DUE TO SPONTANEOUS COMBUSTION HAZARD. ALWAYS SEAL AN ENTIRE SECTION OR THE LENGTH OF A SET OF BOARDS BEFORE MOVING TO THE NEXT SECTION OR SET OF BOARDS (DO NOT "CHECKERBOARD"). DO NOT SEAL PRIOR TO RAIN OR WET SEALED SURFACES BEFORE 72 HOURS OF DRY TIME AS WATER SPOTTING MAY OCCUR, ESPECIALLY ON HORIZONTAL SURFACES LIKE DECKS AND FURNITURE. AVOID USING TRAFFIC AREAS FOR THE FIRST 48 TO 72 HOURS OF DAYTIME.

Other Issues: Mix product cans of different batch numbers, different colors, or old and new product together before use. Do not cover recently sealed surfaces; allow to dry fully exposed. Do not apply over caulks as chemical incompatibilities may occur; caulk over our Sealer only after 30 days dry time (and pre-test compatibility of caulk for adhesion). Surfaces may be slippery when freshly sealed, particularly when wet. Apply carefully- overspray or spillage can damage plants and is not removable from concrete or painted surfaces. Also, OUR SEALER is petroleum-based and you may notice an odor during the first weeks of dry time. ALWAYS TEST A REPRESENTATIVE AREA TO VERIFY SATISFACTION PRIOR TO FULL SCALE APPLICATION.

APPLICATION SUMMARY: 1) Remove prior finishes well. 2) Seal porous, dry wood only. 3) Don't over or under apply- what does not soak in, get off prior to letting dry, ESPECIALLY ON HORIZONTAL SURFACES. By following these instructions, your job will then dry the quickest, look the best, weather the best and be the easiest to re-do when that time comes.

MAINTENANCE: For maximum protection and aesthetic appeal, re-application should take place every 1 to 2 years on decks and horizontal surfaces, every 3 to 4 years on siding, shingles, log homes and vertical surfaces. Hardwoods such as Mahogany and others may require more frequent maintenance. For best results, follow "preparation" instructions above prior to re-applying in subsequent years - just "re-coating" is not recommended as unsatisfactory film build up and discoloration will occur.